DC/DC CONVERTER WITH DEPLETION MODE COMPOUND SEMICONDUCTOR FIELD EFFECT TRANSISTOR SWITCHING DEVICE

Related Applications

5

[0001]   This application is related to co-pending U.S. patent application 10/_____, Attorney Docket No. ONS00501, entitled "VERTICAL COMPOUND SEMICONDUCTOR FIELD EFFECT TRANSISTOR STRUCTURE", by Peyman Hadizad, assigned to the same assignee, Semiconductor Components Industries, LLC, filed concurrently herewith, and which is incorporated by reference for all purposes.

[0002]   This application is further related to co-pending U.S. patent application 10/_____, Attorney Docket No. ONS00505, entitled "METHOD OF MAKING A VERTICAL COMPOUND SEMICONDUCTOR FIELD EFFECT TRANSISTOR DEVICE", by Peyman Hadizad, assigned to the same assignee, Semiconductor Components Industries, LLC, filed concurrently herewith, and which is incorporated by reference for all purposes.

Background of the Invention

25

[0003]   This invention relates generally to high frequency power semiconductor applications, and more specifically to dc/dc converters using field effect transistor (FET) switching devices.

[0004]   In the area of computer and peripheral power supply applications, there are several factors driving future performance and demand. Such factors include an increase in output power requirements because of higher microprocessor speeds, smaller system size (i.e., reduced circuit board space), lower cost, improved transient response, and lower output voltage ripple (i.e., lower microprocessor operating voltages). Additionally, advancing microprocessor needs, which include decreasing operating voltage and increasing current requirements,

will require power conversion devices and circuits that enable highly efficient and tightly regulated power. These devices and circuits must operate at higher frequencies and exhibit enhanced thermal characteristics.

[0005] Electronic systems such as computer and peripheral power supply applications often require that multiple dc voltage levels be produced from a single dc voltage source. This conversion is done with electronic circuits such as dc/dc converters. A basic converter circuit is a two-port network having a pair of input terminals and a pair of output terminals. A dc power source is coupled across the two input terminals, and a dc load is coupled across the two output terminals. Within the two-port network, the circuit typically comprises multiple switching devices, appropriate control circuitry, one or more capacitors, and one or more inductors. Typical dc/dc converters include the buck converter, the boost converter, and the buck-boost converter.

[0006] An ideal switching device has two states: on and off. In the on state, the ideal device conducts current between two terminals with zero voltage drop across the terminals. In the off state, the ideal device will support any voltage drop across the terminals while conducting zero current between them. A number of different semiconductor devices are used as switches in dc/dc converters, all of which depart from the ideal switching device in one or more ways. Examples of such devices include diodes, bipolar transistors, MOSFETs, silicon controlled rectifiers, and junction field effect transistors.

[0007] One problem with typical switching devices is a non-zero voltage between the terminals when in the on state. This results in power dissipation in the switching device, which generates heat and reduces overall circuit efficiency. A second problem involves

the dynamic characteristics of the switching device when transitioning between the on state and the off state. Slow switching speeds place a limit on system operating frequency and duty cycle. Each time a device switches between states, a certain amount of energy is lost. The slower a device switches, the greater the energy lost in the circuit. This has significant impact on high frequency and/or high power applications, and contributes significantly to the reduction of overall efficiency of a dc/dc converter.

[0008]   Most losses in switching power circuits are determined by the physical properties of semiconductor devices. Although silicon based MOSFET devices are a primary choice for many power conversion applications, they have inherent limitations for high frequency applications due to their physical structure. Such limitations include high reverse recovery charge, high gate charge, and high on resistance, which detrimentally impact power dissipation and thermal response characteristics.

[0009]   Multi-phase dc/dc conversion is a preferred technique for addressing the high current/low operating voltage requirements of present and future microprocessors. In multiphase dc/dc converter architectures, a load is distributed evenly across phase-shifted pulse-width-modulation (PWM) channels and associated switching devices and inductors. This approach spreads power and current dissipation across several power handling devices thereby lowering stress on components. This approach also reduces output ripple on inductor current.

[0010]   By way of example, a typical silicon-based multi-phase dc/dc converter for a 120 Amp, 500 kHz microprocessor system consists of four phases. A silicon-based multi-phase dc/dc converter for 1 MHz/120 Amp microprocessor system may consist of five phases, and

a silicon-based multi-phase dc/dc converter for a 2 MHz/120 Amp system may consist of seven phases.

[0011] In multi-phase dc/dc converters, current levels are often sensed in each phase as a means of feedback control within a system. This is done typically using on-resistance of a silicon switching MOSFET device or series resistance of an output inductor. The on-resistance method current sensing is problematic due to variations in processing for silicon MOSFETs devices, which becomes even more of a problem at higher current levels. Additionally, with improvements in inductor designs and fabrication methods, the series resistance current sensing technique has become less reliable because the improvements make it difficult to distinguish the inductor resistance from system noise.

[0012] Accordingly, a need exists for power conversion systems suitable for the increasingly stringent demands of computer and peripheral power supply applications. Additionally, it would beneficial for such systems to include cost effective and reliable switching devices.

Brief Description of the Drawings

[0013] FIG. 1 illustrates, an enlarged cross-sectional view of a portion of a preferred vertical FET device for use with the present invention;

[0014] FIG. 2 illustrates a partial top plan view of a gate control structure for device of FIG. 1;

[0015] FIG. 3 illustrates an enlarged cross-sectional view of a portion of an edge termination structure for the device of FIG. 1;

[0016] FIG. 4 illustrates a circuit diagram of a dc/dc buck converter according to the present invention incorporating a device of FIG. 1; and

[0017]   FIG. 5 illustrates a circuit diagram of a dc/dc boost converter according to the present invention incorporating a device of FIG. 1.

Detailed Description of the Drawings

[0018]   In general, the present invention pertains to a dc/dc power conversion circuit or network that includes at least one compound semiconductor depletion mode junction field effect transistor (JFET) structure. In a preferred embodiment, the circuit includes at least one GaAs depletion mode FET as a switching device. The switching device reduces gate charging effects, gate resistance effects, reverse recovery times, and on resistance thereby improving power conversion performance.

[0019]   Unlike silicon, GaAs is a direct bandgap compound semiconductor material with an inherent property of high electron mobility (8500 cm^2/V-sec), which is greater than 4X that of silicon (1500 cm^2/V-sec). Also, GaAs has a larger bandgap of 1.42 eV compared to 1.1 eV for silicon, which provides, among other things, enhanced performance at elevated temperatures. Additionally, the reverse recovery charge of a GaAs FET device is approximately 100X lower than that of a silicon FET device.

[0020]   The present invention is better understood by referring to FIGS. 1-5 together with the following detailed description. For ease of understanding, like elements or regions are labeled the same throughout the detailed description and FIGURES where appropriate. Although the embodiments shown and described include an n-channel depletion mode FET device, the system according to the present invention is suitable for p-channel devices as well.

(

[0021]   FIG. 1 shows an enlarged cross-sectional view of a vertical FET device or compound semiconductor vertical FET or JFET structure or switching device 11. Structure 11 comprises a body of semiconductor material 13, which preferably includes a starting or supporting substrate or wafer 14 having an upper surface 16. An epitaxial or drift layer or layers 17 is formed on upper surface 16. Body of semiconductor material 13 includes an upper or source surface 19 and a lower or opposing surface 21. Preferably, body of semiconductor material 13 comprises a compound semiconductor such as GaAs, InP or the like. Although only a portion of a FET device or cell is shown, structure 11 comprises a plurality of individual vertical FET devices or cells connected in parallel.

[0022]   In a preferred embodiment for an n-channel depletion mode (i.e., normally on) device, substrate 14 comprises n-type GaAs, and layer 17 comprises an n-type GaAs epitaxial layer, which preferably has a lower dopant concentration than substrate 14. The thickness and dopant concentration of layer 17 varies as a function of the desired device characteristics. Preferably, for a depletion mode FET device, layer 17 has a dopant concentration on the order of less than 5×10^{17} atoms/cm^3 and a thickness greater than about 0.1 microns. Layer 17 is formed using conventional compound semiconductor epitaxial growth methods. The dopant profile of layer 17 is substantially constant, or the profile is graded depending on desired device characteristics. Alternatively, body of semiconductor material 13 comprises InP.

[0023]   Source regions 26 are formed in and extend from upper surface 19. When layer 17 comprises an n type material, source regions 26 comprise n+ regions and preferably are formed using ion implantation techniques. For example, source regions 26 are formed using Si$^+$

implantation at a dose sufficient to lower contact
resistance to subsequently formed contact layers. For
example, a Si^+ dose of about 4.0×10^{13} atoms/cm^2 with an
implant energy on the order of 85 KeV being typical.
5 Alternatively, selenium, tin, or tellurium is used to
form source regions 26. In an alternative embodiment,
multiple source implants at different implant doses and
implant energies are used.

[0024]   Structure 11 further includes a double trench
10 gate, double groove gate, multiple trench gate, trench
within a trench gate, or stepped trench gate structure 28
formed in and extending from upper surface 19 into layer
17. Preferably, trench structure 28 includes a first
trench or groove portion 29 having a width 31 in a range
15 from about 0.3 microns to about 1.5 microns, and a depth
32 in a range from about 0.5 microns to about 5 microns.

[0025]   Trench structure 28 further includes a second
trench or groove portion 34 having a width 36 in a range
from about 0.25 microns to about 1.4 microns, and a depth
20 37 in a range from about 0.5 microns to about 5 microns.
Preferably, the pitch or centerline-to-centerline
distance 41 of adjacent trench gate structures 28 is in a
range from about 1.3 to about 4.5 microns. These
dimensions are variable according to specific device
25 requirements. That portion of layer 17 between gate
structures 28 forms channels or channel regions 61.

[0026]   Structure 11 also includes doped gate regions
59, which preferably extend along sidewalls and lower
surfaces of second trenches 34. For an n-channel device,
30 doped gate regions 59 are p-type, and are formed
preferably using angled ion implantation. Preferably,
gate regions 59 and source regions 26 are activated using
rapid thermal processing with a temperature up to about
900°C for about 10 to 30 seconds being sufficient.

35 [0027]   Trench structures 28 preferably are formed
using reactive ion etching (RIE) or damage free electron

cyclotron resonance (ECR) etching, which provides clean
and straight sidewall features. A chlorine-based etch
chemistry is preferred. In a preferred embodiment,
second trench 34 is formed using spacers formed on the
5   sidewalls of first trench 29, which are subsequently
removed.

[0028]   A dielectric or passivation layer 63 is formed
over upper surface 19 including trench structures 28.
Preferably, passivation layer 63 comprises a silicon
10   nitride with a thickness in a range from about 0.05
microns to about 0.3 microns. Preferably, plasma
enhanced chemical vapor deposition (PECVD) is used to
form passivation layer 63. A dielectric layer is then
formed over passivation layer 63, and planarized to form
15   a trench-fill layer 66. Trench-fill layer 66 provides
for, among other things, better step coverage for
subsequently formed conductive layers, and preferably
comprises a low temperature oxide, silicon nitride, or a
spin on dielectric. Trench-fill layer 66 is formed using
20   etch-back or chemical mechanical planarization (CMP)
techniques.

[0029]   Openings are then formed in dielectric layer 63
to provide contacts to source regions 26. Additionally,
portions of trench-fill layer 66 and passivation layer 63
25   are removed to expose portions of a gate connecting
region 79 (shown in FIG. 2). A first metal or contact
layer formed over upper surface 19, and patterned to
provide a source contact 84 and a gate contact 86 (shown
in FIG. 2). Source contact layer 84 and gate contact
30   layer 86 preferably comprise NiGeAu, NiGeW, or other
suitable metal. A second contact layer or metal layer 87
is formed over source contact 84 and gate contact 86.
Second metal layer 87 preferably comprises nickel or
gold, and is formed using electroplating or electroless
35   plating techniques. Body of semiconductor material 13 is
thinned using a backgrind step, and a back metal or drain

contact layer 88 is deposited on lower surface 21. Drain contact layer 88 comprises NiGeAu, or another suitable metal.

[0030]   FIG. 2 shows an enlarged partial top plan view of a preferred gate contact structure 71, which includes doped connecting region 79. Doped gate connecting region 79 ties or couples together a plurality of doped gate regions 59 in a single contact region. For ease of understanding, structure 11 shown in FIG. 1 is taken along reference line 1-1 of FIG. 2. Phantom line 89 represents an alternative placement for gate contact layer 86. Doped termination region 159 and termination contact layer 186 is part of a preferred termination structure 91, which is described next in FIG. 3.

[0031]   Termination structure 91 is formed on a periphery or perimeter of vertical FET structure 11. Structure 91 includes a termination region 159 that is formed at the same time as doped gate regions 59, and comprises the same conductivity type (e.g., p-type when structure 11 comprises an n-channel device). Termination structure 91 provides a means for controlling electric field spread and electric field shape during device operation, and preferably is coupled to gate connecting region 79 as shown in FIG. 2.

[0032]   By using multiple trench structure 28 according to the present invention, gate region 59 is placed deeper into channel regions 61 and is more separated from source regions 26 thereby improving gate blocking characteristics. Also, by using a doped gate region, the blocking characteristics are further improved compared to conventional Schottky gate designs. Also, because structure 11 comprises a compound semiconductor material, structure 11 has a reduced gate charge, reduce gate resistance, and enhanced switching speeds compared to silicon based devices.

[0033] In addition, for a given output current and switching frequency, structure 11 dissipates less power thereby allowing one to use a smaller chip size and a reduced number of phases. Additionally, by using a

5 reduced width second trench 34 and gate connecting regions 79 to couple a plurality of gate regions together, the plurality of doped gate regions 59 are placed close together thereby improving device performance. Moreover, compound semiconductor structure

10 11 provides a preferred depletion mode or normally on FET device that has advantages for advanced multi-phase power conversion applications because, among other things, a depletion mode device has a lower series resistance compared to an enhancement mode device.

15 **[0034]** Furthermore, structure 11 can handle more current per phase in a multiphase power conversion application compared to silicon-based or enhancement mode devices. For example, for a 120A/500 kHz application, three phases are required with structure 11 compared to

20 four for a silicon-based device. For a 120A/1 MHz application, four phases are required with structure 11 compared to 5 for a silicon-based device. For a 120A/2 MHz application, four phases are sufficient using structure 11 compared to seven for a silicon-based

25 device. This also enables a smaller system size thereby saving on pc board space, which makes the structure according to the present invention a cost effective alternative for high power/high frequency applications.

[0035] Turning now to FIG. 4, a dc/dc buck converter

30 circuit 71 according to the present invention is described. Circuit 71 includes at least one n-channel depletion mode or normally on compound semiconductor FET device. Converter circuit 71 is a two-port network having a positive input terminal 710, a positive output

35 terminal 730, and a negative input terminal 720 connected to a negative output terminal 740. In a preferred

embodiment described hereinafter, circuit 71 includes two

n-channel depletion mode compound semiconductor FET

devices 711 and 712. Alternatively, at least one of FETs

711 and 712 comprise an n-channel depletion mode compound

5   semiconductor FET device. Preferably dc/dc converter

circuit 71 comprises switching FET devices 711 and 712

based on semiconductor double trench vertical FET

structure 11 shown in FIG. 1.

[0036]   First n-channel depletion mode compound

10   semiconductor vertical FET or switch 711 is connected

between positive input terminal 710 and an internal node

795. Second n-channel depletion mode compound

semiconductor vertical FET or switch 712 is connected

between internal node 795 and common negative terminals

15   720 and 740. A gate driver or control circuit 780 is

connected to the gate leads of first FET 711 and second

FET 712, and functions to switch FETs 711 and 712 between

current conducting and current blocking states. One or

more inductors 760 are connected between internal node

20   795 and positive output terminal 730. A cathode of a

rectifier diode 750 is connected to internal node 795,

and an anode is connected to common negative terminals

720/740. A capacitor or capacitors 770 is connected

across output terminals 720/740.

25   [0037]   Control circuit 780 generates two switching

signals with a delay between them. One control signal is

applied to the gate of first n-channel depletion mode FET

711, and the second control signal is applied to the gate

of second n-channel depletion mode FET 712 in order to

30   switch the two FET devices on and off. The phase

difference between the two control signals ensures that

one FET device is always in a non-conducting state. When

FET device 711 is in a current conducting state, FET

device 712 is held in a current blocking state and vice

35   versa. Under this condition, a voltage source placed

across input terminals 710 and 720 causes a dc current in

a path entering positive input terminal 710, passing
through first n-channel depletion mode FET 711 and
inductor 760, and capacitor 770 out positive output
terminal 730 through a load (not shown), into negative
5   output terminal 740, and out negative input terminal 720
returning to the voltage source.

[0038]   When first n-channel depletion mode FET device
711 is in a current blocking state, second n-channel
depletion mode FET device 712 is held in a current
10 conducting state. Under this condition, energy stored in
inductor 760 causes a dc current to flow through inductor
760, through capacitor 770 and out positive output
terminal 730 and through a load (not shown). The current
path proceeds through negative output terminal 740
15 through second n-channel depletion mode FET 712 back to
inductor 760.

[0039]   Control circuit 780 is operated, for example,
as a pulse width modulator that controls the level of dc
output voltage. Control waveforms applied to the gate
20 leads of depletion mode FET devices 711 and 712 can be
considered a series of negative pulses in which a
negative pulse switches an n-channel depletion mode FET
device into a current blocking state. The dc output
voltage is then proportional to the ratio of negative
25 pulse time to waveform period time. Holding the waveform
in a high state holds a depletion mode FET device in a
current blocking state, while holding the waveform in a
low state holds a depletion mode FET device in a current
conducting state. One advantage of circuit 71 is that it
30 is not dependent on synchronization with a transformer
voltage with gate drive signals for control and
synchronous FET devices.

[0040]   Turning now to FIG. 5, a dc/dc boost converter
circuit 81 according to the present invention is
35 described. Circuit 81 includes at least one n-channel
depletion mode or normally on compound semiconductor

device. Converter circuit 81 is a two-port network
having a positive input terminal 810, a positive output
terminal 830, and a negative input terminal 820 connected
to a negative output terminal 840. In a preferred

5   embodiment described hereinafter, circuit 81 includes two
n-channel depletion mode compound semiconductor FET
devices 811 and 812. Alternatively, at least one of FETs
811 and 812 comprise an n-channel depletion mode compound
semiconductor FET device. Preferably dc/dc converter

10   circuit 81 comprises switching FET devices 811 and 812
based on semiconductor double trench vertical FET
structure 11 shown in FIG. 1.

[0041]   First n-channel depletion mode compound
semiconductor vertical FET or switch 811 is connected

15   between positive output terminal 830 and an internal node
895. Second n-channel depletion mode compound
semiconductor vertical FET or switch 812 is connected
between internal node 895 and common negative terminals
820 and 840. A gate driver or control circuit 880 is

20   connected to the gate leads of first FET 811 and second
FET 812, and functions to switch FETs 811 and 812 between
current conducting and current blocking states. One or
more inductors 860 are connected between internal node
895 and positive input terminal 810. A capacitor or

25   capacitors 870 is connected across output terminals
820/840.

[0042]   Control circuit 880 generates two switching
signals with a delay between them. One control signal is
applied to the gate of first n-channel depletion mode FET

30   811, and the second control signal is applied to the gate
of second n-channel depletion mode FET 812 in order to
switch the two FET devices on and off. The phase
difference between the two control signals ensures that
one FET device is always in a non-conducting state.

35   [0043]   When first FET device 811 is in a current
conducting state, second FET device 812 is held in a

current blocking state. Under this condition, a voltage source placed across input terminals 810 and 820 causes a dc current in a path entering positive input terminal 810, passing through inductor 860 through first n-channel

5   depletion mode FET 811 and capacitor 870 out positive output terminal 830 through a load (not shown), into negative output terminal 840, and out negative input terminal 820 returning to the voltage source.

[0044]   When first n-channel depletion mode FET device

10   811 is in a current blocking state, second n-channel depletion mode FET 812 is held in a current conducting state. Under this condition, FET 812 is switched on and current flows from input terminal 810 through inductor 860 and FET 812, which ramps up the inductor current.

15   Once FET 812 is switched off, the voltage on its drain rises and it forward biases the body diode of FET 811. The body diode then starts to conduct the inductor current.

[0045]   After a dead time delay, control circuit 880

20   sends a gate signal to FET 811, which turns FET 811 on. In this mode the inductor current is diverted from the body diode to the channel region of FET 811. Once FET 811 is switched off, its body diode conducts once more until the dead time lapses and FET 812 is switched on.

25   For a short time afterwards, the reverse recovery charge of FET 811 diode is dissipated through FET 812. FET 812 is now on once more, and the cycle repeats itself.

[0046]   Control circuit 880 is operated, for example, as a pulse width modulator that controls the level of dc

30   output voltage. Control waveforms applied to the gate leads of depletion mode FET devices 811 and 812 can be considered a series of negative pulses in which a negative pulse switches an n-channel depletion mode FET device into a current blocking state. The dc output

35   voltage is then proportional to the ratio of negative pulse time to waveform period time. Holding the waveform

in a high state holds a depletion mode FET device in a
current blocking state, while holding the waveform in a
low state holds a depletion mode FET device in a current
conducting state.

5 **[0047]**   Thus it is apparent that there has been
provided, in accordance with the present invention, a
dc/dc power converter including a depletion mode compound
semiconductor FET switching device. The switching device
reduces gate charging effects, gate resistance effects,

10 reverse recovery times, and on resistance thereby
improving power conversion performance.

[0048]   Although the invention has been described and
illustrated with reference to specific embodiments
thereof, it is not intended that the invention be limited

15 to these illustrative embodiments. For example, the
structure according to the present invention is suitable
for other power conversion systems. Additionally,
although an n-channel depletion mode switching device is
shown, a p-channel depletion mode device is suitable.

20 Those skilled in the art will recognize that
modifications and variations can be made without
departing from the spirit of the invention. Therefore,
it is intended that this invention encompass all such
variations and modifications as fall within the scope of

25 the appended claims.